



AUTOMATED MOUNTING SOLUTIONS

Engineered with quality and ease of installation, Chief's state-of-the-art Cinematic mounts combine top quality mounting solutions with motorized, remote operation. The Cinematic Series offers programmable viewing angles and fast, fine-tuned adjustments. Solid steel construction and carefully engineered electronics put these products in a class of their own!



AUTOMATED MOUNTING SOLUTIONS*

FLAT PANEL MOUNTS



CM1W18™ ■ SWING ARM MOUNT 37 - 61"

FEATURES

MULTIPLE CONTROL OPTIONS

Control options include: serial communication, three programmable viewing options, and IR remote (included).

Q-LATCH™ MOUNTING SYSTEM

Flat panel secures to mount with a latching flag. Easy to connect/disconnect – no tools needed!

SPECIFICATIONS

Extension 4.25-18" (108-457 mm)

Weight Capacity 170 lbs (77.1 kg)

Swivel* up to ±50°

Color Black

**Swivel range varies depending on screen size.*



(CM2C40 Ceiling Lift) (CM2L40 Pop-Up Lift)

CM2C40™ /CM2L40™ ■ LIFT 32 - 61"

FEATURES

AUTODRIVE™ SYSTEM

Ultra fast and quiet travel at over 2" (51 mm) per second with preset viewing position.

TELESCOPING DESIGN

Collapses to a stored height of 31" (790 mm) with approximately 40" (101.6 cm) of travel.

SPECIFICATIONS

Extension 31-71" (79-180 cm)

Weight Capacity 170 lbs (77.1 kg)

Color Black



CM3T45™ ■ SWIVEL TABLE STAND 32 - 50"

FEATURES

AUTOMATED SWIVEL

Up to 45° of swivel left/right with optional stops at 25° and 35° for optimal viewing angles.

HEIGHT ADJUSTMENT

Allows 5" (127 mm) of adjustment for screen heights up to 32" (813 mm).

SPECIFICATIONS

Swivel +/-45°

Height Adjustment 5" (127 mm)

Weight Capacity 125 lbs (56.7 kg)

Color Black, Silver



CM4S57™ ■ SPEAKER ADAPTER 37 - 63"

FEATURES

AUDIO SEPARATION

Up to 4.5' (137 cm) speaker extension for an amazing home theater effect.

ADVANCED CABLE MANAGEMENT

Integrated speaker wire and gold-plated binding posts with multiple connection options including screw-on or push-in.

SPECIFICATIONS

Extension Up to 9' (274.3 cm)

Weight Capacity 220 lbs (99 kg) total
22 lbs (10 kg) per speaker

Color Black

CM5V42™ ■ ART LIFT 32 - 42"



FEATURES

EASY ART ATTACHMENT

Bracket included to quickly hang and secure artwork.

ULTRA QUIET MOVEMENT

Up to 28.2" (716 mm) of smooth travel.

IR REPEATER

For use with existing remote.

SPECIFICATIONS

Extension	Up to 28.2" (716 mm)
Depth	4.6-7.6" (116-192 mm)
Minimum Art Size	42 x 38" 106.7 x 96.5 cm
Weight Capacity	15 lbs (6.8 kg)
Color	Black

CM6™ ■ CABINET ACCESSORIES

FEATURES

EASY INSTALLATION

Ships with motor box pre-mounted onto track for quick and easy installation.

AUTOMATED LIGHT CONTROL

Lighting can be dimmed by remote control.

INTEGRATED SAFETY CONTROL

Motor stops and reverses doors if travel is obstructed.

MODELS AVAILABLE*

CM6SV	Single Vertical
CM6DV	Dual Vertical
CM6DH	Dual Horizontal
CM6QH	Quad Horizontal

*Visit www.chiefmfg.com for more information and specs.



(CM6QH)

CM7W12U™ ■ SWING ARM 37 - 63"

FEATURES

PRESET POSITIONS

Two preset buttons on remote to program favorite viewing positions.

MULTIPLE CONTROL OPTIONS

Control options include: RS232 interface, two programmable viewing options, and IR remote (included).

SPECIFICATIONS

Extension	4.6-12" (117-305 mm)
Tilt	+7°, -20°
Swivel	Up to 28° left/right
Weight Capacity	180 lbs (81.6 kg)
Color	Black



NEW CM8T15U™ ■ TILT MOUNT

FEATURES

AUTOMATED TILT

Provides +2°/-13° of smooth, motorized tilt when display is powered on. Mount automatically returns to low-profile, flush position when TV is turned off.

LOW PROFILE

Only 3.6" (91 mm) from the wall when in home position.

SPECIFICATIONS

Dimensions (HxWxD)	23.6" x 29" x 3.6" (601 x 737 x 91 mm)
Tilt	+2°, -13°
Mounting Pattern Width	10.2" - 30.1" (259 - 765 mm)
Mounting Pattern Height	up to 19.3" (490 mm)
Weight Capacity	150 lbs (68 kg)





AUTOMATED MOUNTING SOLUTIONS

PROJECTOR MOUNTS AND ACCESSORIES



SL151™ ■ SMART-LIFT*

FEATURES

OPTIMIZED TILE INSTALLATION

Replaces 2' x 2' (600 x 600 mm) tile for fast installations.

QUICK CONNECT/DISCONNECT

Convenient lamp and filter access on most projectors. Maintains registration even when disconnected.

LOW PROFILE

Requires only 11" (279 mm) of clearance above ceiling. Provides 8.25" (210 mm) of downward travel.

* Requires SLB interface bracket.

SPECIFICATIONS

Extension	8.5" (216 mm)
Max Projector Size (HxWxD)	8.38 x 18 x 18.25" (213 x 457 x 464 mm)
Ceiling Opening (HxWxD)	11.25 x 23 x 22.75" (286 x 584 x 578 mm)
Ceiling Closure (WxD)	20.25 x 20.25" (514 x 514 mm)
Roll/Pitch/Yaw	+/-2°, +/-20°, +/-5°
Weight Capacity	35 lbs (15.9 kg)
Color	White



SL236™ ■ SMART-LIFT*

FEATURES

EXTENDED TRAVEL

Requires only 11" (279 mm) of clearance above ceiling for 36" (91.4 mm) of downward travel with three stopping positions.

PRECISE POSITIONING

Vertical projector cradle adjustment and fore/aft, left/right projector positioning.

QUICK CONNECT/DISCONNECT

Convenient lamp and filter access on most projectors. Maintains registration even when disconnected.

* Requires SLB interface bracket.

SPECIFICATIONS

Extension	36" (914 mm)
Max Projector Size (HxWxD)	9.25 x 20.5 x 22.75" (279 x 635 x 698 mm)
Ceiling Opening	25.5 x 28" (641 x 710 mm)
Ceiling Closure	24 x 24" (610 x 610 mm)
Roll/Pitch/Yaw	+/-2°, +/-15°, +/-10°
Weight Capacity	35 lbs (15.9 kg)
Color	White



RECOMMENDED ACCESSORIES

IR10™ ■ Infrared Remote

RC10™ ■ Radio Frequency Remote

SLB™ ■ Projector Interface Bracket

(Required for SL151 and SL236 Smart-Lifts)

SS10™ ■ Pressure-Sensitive Safety Strip

ST15™ ■ Safety Strip Terminals

PACLR1™ ■ Side Speaker Adapters

PACCC1™ ■ Center Speaker Adapter

end-user focused

faster installation

superior service

proven quality

CHIEF MANUFACTURING

■ A DIVISION OF MILESTONE AV TECHNOLOGIES ■ www.chiefmfg.com

USA/INTERNATIONAL

■ P 800.582.6480/952.894.6280 ■ F 877.894.6918/952.894.6918 ■ chief@chiefmfg.com

CHIEF MOUNTS CANADA

■ P 877.345.4329 ■ F 888.377.5314 ■ info@chiefmounts.ca

MILESTONE EUROPE B.V.

■ P 31 (0)40 2668620 ■ F 31 (0)40 2668615 ■ europe@milestone.com

MILESTONE ASIA PACIFIC LTD

■ P 86 755 8996 9226 ■ F 86 755 8996 9217 ■ asia.chief@milestone.com

©2008 Milestone AV Technologies, a Duchossois Group Company. 700007B 8/08. Chief is a registered trademark of Milestone. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.